

Singapore Management University

## Institutional Knowledge at Singapore Management University

---

Research Collection School Of Computing and  
Information Systems

School of Computing and Information Systems

---

7-2019

### Simulated annealing for the single-vehicle cyclic inventory routing problem

Aldy GUNAWAN

Singapore Management University, [aldygunawan@smu.edu.sg](mailto:aldygunawan@smu.edu.sg)

Vincent F. YU

Audrey T. WIDJAJA

Pieter. VANSTEENWEGEN

Follow this and additional works at: [https://ink.library.smu.edu.sg/sis\\_research](https://ink.library.smu.edu.sg/sis_research)



Part of the [Artificial Intelligence and Robotics Commons](#), and the [Theory and Algorithms Commons](#)

---

#### Citation

GUNAWAN, Aldy; YU, Vincent F.; WIDJAJA, Audrey T.; and VANSTEENWEGEN, Pieter.. Simulated annealing for the single-vehicle cyclic inventory routing problem. (2019). *GECCO '19: Proceedings of the Genetic and Evolutionary Computation Conference Companion, Prague, Czech Republic, 2019 July 13-17*. 1-2.

Available at: [https://ink.library.smu.edu.sg/sis\\_research/4473](https://ink.library.smu.edu.sg/sis_research/4473)

This Conference Proceeding Article is brought to you for free and open access by the School of Computing and Information Systems at Institutional Knowledge at Singapore Management University. It has been accepted for inclusion in Research Collection School Of Computing and Information Systems by an authorized administrator of Institutional Knowledge at Singapore Management University. For more information, please email [cherylids@smu.edu.sg](mailto:cherylids@smu.edu.sg).

# Simulated Annealing for the Single-Vehicle Cyclic Inventory Routing Problem

Aldy Gunawan

Singapore Management University  
Singapore, Singapore  
aldygunawan@smu.edu.sg

Audrey Tedja Widjaja

Singapore Management University  
Singapore, Singapore  
audreyw@smu.edu.sg

Vincent F. Yu

National Taiwan University of Science and Technology  
Taipei, Taiwan  
vincent@mail.ntust.edu.tw

Pieter Vansteenwegen

KU Leuven  
Leuven, Belgium  
pieter.vansteenwegen@kuleuven.be

## ABSTRACT

This paper studies the Single-Vehicle Cyclic Inventory Routing Problem (SV-CIRP) with the objective of simultaneously minimizing distribution and inventory costs for the customers and maximizing the collected rewards. A subset of customers is selected for the vehicle, including the quantity to be delivered to them. Simulated Annealing (SA) is proposed for solving the problem. Experimental results on 50 benchmark instances show that SA is comparable to the state-of-the-art algorithms. It is able to obtain 12 new best known solutions.

## CCS CONCEPTS

• **Theory of computation** → **Approximation algorithms analysis**; **Simulated annealing**;

## KEYWORDS

Metaheuristics, Simulated Annealing, Cyclic Inventory Routing Problem

### ACM Reference Format:

Aldy Gunawan, Vincent F. Yu, Audrey Tedja Widjaja, and Pieter Vansteenwegen. 2019. Simulated Annealing for the Single-Vehicle Cyclic Inventory Routing Problem. In *Proceedings of the Genetic and Evolutionary Computation Conference 2019 (GECCO '19 Companion)*. ACM, New York, NY, USA, Article 4, 2 pages. <https://doi.org/10.1145/3319619.3321888>

## 1 INTRODUCTION

In the traditional supply chain context, supplier and customers independently make their decisions on replenishing the inventory. Vendor Managed Inventory (VMI) was introduced later [5] to synchronize different activities. The Inventory Routing Problem (IRP), which is a VMI problem [4], considers both managing the inventories at the customers and distributing products from a central depot

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](mailto:permissions@acm.org).

GECCO '19 Companion, July 13–17, 2019, Prague, Czech Republic

© 2019 Copyright held by the owner/author(s). Publication rights licensed to the Association for Computing Machinery.

ACM ISBN 978-1-4503-6748-6/19/07...\$15.00

<https://doi.org/10.1145/3319619.3321888>

to the customers. The supplier manages the routing of vehicles distributing the products and the timely replenishment of inventories at the customers as well [1]. Cyclic IRP (CIRP) is a variant of IRP where customer demand rates are stable with an infinite planning horizon. The main objective is to find a cyclic distribution plan for a set of customers with the objective of minimizing long-term transportation and inventory costs [3]. The vehicles are allowed to perform multiple trips on a single day.

In Single-Vehicle CIRP (SV-CIRP), a special case of CIRP, visiting all customers is not compulsory and a vehicle is allowed to make multiple trips from the depot within one cycle. The cycle time represents the time between two deliveries to each customer. A reward occurs for each visited customer. The objective is to simultaneously minimize transportation and inventory costs and maximize the collected rewards from visited customers [7]. Simulated Annealing (SA) is designed to solve the problem.

## 2 THE SV-CIRP

We consider an undirected network graph  $G = (S^+, A)$ , where  $S^+ = \{0, 1, 2, \dots, |S|\}$  is the set of nodes, and  $A = \{(i, j) : i \neq j \in S^+\}$  refers to the set of arcs connecting two different nodes  $i$  and  $j$ . Let  $S = S^+ \setminus \{0\}$  be a set of potential customers. Node 0 represents the depot. Each customer  $j$  has an inventory cost  $\eta_j$  (price/(time $\times$ quantity)), a handling cost  $\phi_j$  (price), a demand rate  $d_j$  (quantity/time) and a fixed reward  $\lambda_j$  (price/time). The reward corresponds to the collected profit when the customer is selected for replenishment. The travel time from customer  $i$  to customer  $j$  is represented by  $t_{ij}$ . The vehicle is assumed to have a fixed operating cost  $\psi$  (price/time), a fixed average vehicle speed  $v$  (distance/time), the travel cost  $\delta$  (price/distance) and the vehicle capacity  $\kappa$  (quantity). It is assumed that each customer has an infinite inventory capacity. The largest possible quantity that can be delivered to customer  $j$  is denoted as  $Q_j^{max}$ , which is calculated as:

$$Q_j^{max} = d_j \times \frac{\kappa}{\min_{j \in S} \{d_j\}} \quad (1)$$

The objective is to minimize the total cost minus the total collected reward. The total cost consists of the transportation, delivery and holding costs. Due to the multiple trips a vehicle can make during one cycle, each one starting from the depot, the total travel time per cycle  $T$  is determined by the sum of all trip travel times. Each trip should respect the vehicle capacity.

### 3 SIMULATED ANNEALING

We calculate  $ratio_{jj'}$  between nodes  $j$  and  $j'$  (Equation 2), which represents the collected reward per distance travelled. We then create a solution representation - a permutation of  $|S|$  customers (Figure 1). Customers are sorted in descending order according to ratio values, starting from  $j = 0$ , until all customers are included. Since it is not mandatory to visit all customers, we select a subset of the visited customers, represented by shaded cells in Figure 1.

$$ratio_{jj'} = \frac{\lambda_{j'}}{t_{jj'} \times v} \quad \forall j, j' \in S^+ \quad (2)$$



Figure 1: An example of a solution representation



Figure 2: Decoding results (a); final route (b)

The solution representation is decoded into a sequence of possible visited customers (2(a)).  $T$  is determined by finding the lower and upper bound values,  $T_{min}$  and  $T_{max}$  [4].  $T_{min}$  is the total travel time required to visit all selected customers, while  $T_{max}$  is calculated by Equation 3. Let  $S'$  be the set of selected customers. When  $T_{min} > T_{max}$ , we recalculate  $T_{min}$  and  $T_{max}$  after removing the customer with the highest demand rate until  $T_{min} < T_{max}$ . The ideal cycle time (the "economic-order-quantity"),  $T_{EOQ}$  [7], is calculated by Equation 4. There are three possible values of  $T$ :  $T = T_{EOQ}$  if  $T_{min} \leq T_{EOQ} \leq T_{max}$ . If  $T_{EOQ} < T_{min}$ , then  $T = T_{min}$ . If  $T_{EOQ} > T_{max}$ , then  $T = T_{max}$ . The vehicle starts the delivery from the depot and sends as much as  $d_j T$  to the selected customer  $j$ . Due to the vehicle capacity constraint, the vehicle may return to the depot to replenish its capacity and continue the trip, as long as the total trip time does not exceed  $T$ . Figure 2(b) illustrates the final route. Customers 7 and 3 cannot be visited due to the time limitation, therefore, they are not shaded.

$$T_{max} = \frac{\kappa}{\max_{j \in S'} d_j} \quad (3)$$

$$T_{EOQ} = \sqrt{\frac{\delta \times v \times T_{min} + \sum_{j \in S'} \phi_j}{\sum_{j \in S'} \frac{d_j \times \eta_j}{2}}} \quad (4)$$

We propose SA with a random neighborhood structure that features various types of moves: SWAP, INSERT, INVERSE, REMOVE and ADD. SWAP is performed by selecting two customers and exchanging their positions. INSERT is done by selecting one customer and inserting it into the position before another randomly selected customer. INVERSE is conducted by selecting two customers and reversing the positions of customers between them. ADD is applied by selecting one non-shaded customer randomly and converting it into shaded customer. REMOVE is the opposite of ADD. Other SA parameters, e.g. initial temperature, are determined to ensure the solution quality.

### 4 EXPERIMENTAL RESULTS

Five sets of benchmark instances are available on <https://www.mech.kuleuven.be/en/cib/op#section-35>. SA was coded in C++ and all experiments were executed on a computer with Intel Core i7-6700 CPU @ 3.40 GHz processor, 16.0 GB RAM. Each instance is solved five times. The results are compared with the best known solutions (BKs), taken from state-of-the-art algorithms: the Steepest Descent Hybrid Algorithm (SDHA) [6], Iterated Local Search (ILS) [7], Iterated Local Search (ILS) [4] and the convex optimization [2].

| Dataset | BKs          |                 | SA           |                 |                 |         |
|---------|--------------|-----------------|--------------|-----------------|-----------------|---------|
|         | Average Cost | Average CPU (s) | Average Cost | Average CPU (s) | Average Gap (%) | New BKS |
| Set 1   | -346.16      | 1.6             | -346.16      | 12.8            | 0.00            | 0       |
| Set 2   | -740.73      | 144.7           | -739.26      | 18.9            | 0.21            | 0       |
| Set 3   | -2182.35     | 1501.2          | -2171.97     | 85.3            | 0.48            | 1       |
| Set 4   | -1041.24     | 6097.3          | -1057.86     | 405             | -1.46           | 5       |
| Set 5   | -1366.04     | 5858.9          | -1372.32     | 414.1           | -0.39           | 6       |

Table 1: Experimental Results

We only summarize the average results in Table 1. For Set 1, SA is able to obtain the optimal solutions. For Set 2, SA results are slightly worse than BKs. SA performs better in solving some instances compared to the results of ILS [4], at the cost of the computational time. For Set 3, SA performs better than ILS [4] in solving four instances: A25-1, A25-2, A25-6 and A25-8. SA improves one best known solution, A25-8. The BKs for Set 4 are obtained by the convex optimization [2]. SA is able to improve 5 BKs. For Set 5, SA also improves 6 solutions of the convex optimization. The best known solutions are further improved by 0.39%, on average, with 6 new BKs.

### 5 CONCLUSIONS

This work proposes Simulated Annealing to solve the SV-CIRP. The experimental results show that SA is comparable to the state-of-the-art algorithms. It finds 12 new BKs. We observe that the computational time remains limited, especially for larger instances. Some possible paths for further research include split deliveries and multiple vehicles.

### REFERENCES

- [1] H. Andersson, A. Hoff, M. Christiansen, G. Hasle, and A. Lokketangen. 2010. Industrial aspects and literature survey: combined inventory management and routing. *Computers and Operations Research* 37 (2010), 1515–1536.
- [2] W. Lefever, E.-H. Aghezzaf, and K. Hadj-Hamou. 2016. A convex optimization approach for solving the single-vehicle cyclic inventory routing problem. *Computers and Operations Research* 72 (2016), 97–106.
- [3] B. Raa and E.-H. Aghezzaf. 2009. A practical solution approach for the cyclic inventory routing problem. *European Journal of Operational Research* 192 (2009), 429–441.
- [4] P. Vansteenwegen and M. Mateo. 2014. An iterated local search algorithm for the single-vehicle cyclic inventory routing problem. *European Journal of Operational Research* 237 (2014), 802–813.
- [5] M. Waller, M.E. Johnson, and T. Davis. 1999. Vendor-managed inventory in the retail supply chain. *Journal of Business Logistics* 20 (1999), 183–203.
- [6] Y. Zhong. 2012. *Exact and heuristic methods for the cyclic inventory routing problem with side-constraints*. Ph.D. Dissertation. Ghent University, Ghent, Belgium.
- [7] Y. Zhong and E.-H. Aghezzaf. 2012. Effective local search approaches for the single-vehicle cyclic inventory routing problem. *International Journal of Services Operations and Informatics* 7 (2012), 260–279.